स्थायी लेखा नं :: २०१२९६१९० कार्यालय कोड नं.: ८०१०५५८०२

ठाकुरबाबा नगरपालिका Thakurbaba Municipality



गर कार्यपालिकाको कार्यालय

Office of the Municipal Executive

(Google Plus Code: C8RJ+C6 Neulapur)

सैनवार, बर्दिया Sainawar, Bardiya

लुम्बिनी प्रदेश, नेपाल Lumbini Province, Nepal

सुचना !!!

सूचना !

सुचना !!

सी.सी टिभि सेट, ए.भि.आर. बोर्ड तथा स्मार्ट टि.भि को दररेट पेश गर्ने सम्बन्धमा।

प्रथम पटक प्रकाशित मितिः २०८१।०२।०१ गते

प्रस्तुत विषयमा यस ठाकुरबाबा नगरपालिका अन्तर्गतको विद्यालयका लागि सी.सी टिभि सेट, ए.भि.आर. बोर्ड तथा स्मार्ट टि.भि खरिद गर्नुपर्ने भएकाले मिति २०८१ | ०२ | ०१ गते देखि मिति २०८१।०२।०७ गतेसम्म (७ दिन भित्रमा) आफुले के कति दर रेटमा पत्रसाथ संलग्न स्पेशिफिकेसन बमोजिम सामाग्रिहरू दिन सिकन्छ सो को दररेट उल्लेख एवम् प्रमाणित गरि स्पेशिफिकेसनमा समेत ब्राण्डको नाम र मोडल नंम्बर उल्लेख गरि प्रमाणित गरि पेश गर्नुहन अनुरोध छ।

नोटः दररेट केबल Project Cost Estimation मा प्रयोग गरिने छ।

प्रमुख प्रशासकीय अधिकत



Thakurbaba Municipality

Office of the Municipal Executive

Sainawar, Bardiya Lumbini province



BoQ of CCTV Camera Set, 75Inches AVR Board, 55Inches Smart TV etc.

S.N.	Particular	Unit	Quantity	Rate	Amount	Remarks
1	Indoor 2MP IP Dome Camera	Nos	28			
2	Outdoor 4MP Bullet Camera	Nos	4			
3	32 Port NVR with 2 SATA	Nos	1			
4	10 TB Surveillance HDD	Nos	1			
5	8 Port PoE Switch With 2 Uplinks Port	Nos	4			
6	UTP CAT6 Cable With Pure Copper	Box	2			
7	9U Rack	Nos	1			
8	75 Inches Digital AVR Board	Nos	11			
9	55 Inches Smart TV	Nos	1			
10	A3 Duplex Printer	Nos	1			
11	Speaker	Nos	2			
12	Mixer Amplifier (including cable to connect to speaker)	Nos	1			
13	Microphones (Wired)	Nos	2			
14	Microphones (Wireless)	Nos	2			
15	OPS	Nos	1			
16	Branded AVR Board Stand (With wheel lock system, capacity: ≥75 Inches)	Nos	1	7		
17	Installation of CCTV (Listic, Wiring and Power Socket, Cable clipping)	Per Unit	32			
18	Installation of Smart TV (Listic, Wiring and Power Socket, Cable clipping)	Per Unit	1			
19	Installation of AVR Board (Listic, Wiring and Power Socket, Cable clipping)	Per Unit	11			
	Total			9		
	VAT 13%					
	Grand Total					

Firm Name:	
Address:	
Name of Representative:	
Signature:	
Date:	
Contact Num.:	

Firm Stamp:



1. Specifications of CCTV Set, HardDisk,NVR,Networking Cable,PoE Switch

SN	Products	Description	
1	2MP Indoor DOM IP	> 2MP, 1/2.8"-2.9" CMOS image sensor, low illuminance, high image	ge
	Camera	definition	
		Maximum resolution 2MP (1920 × 1080) @25/30 fps	
	D 1.	► H.265+/ H.264+&H.264 codec, high compression rate, ultra-low b	it rate
	Brand:	 Built-in efficient IR illuminator, and the IR range up to 30 m Focal length: > 2.8mm 	
		 Focal length: ≥ 2.8mm Wide Dynamic Range (WDR): Digital WDR 	
	M- 1-1.	 Day/Night Switch: Day, Night, Auto, Schedule 	
	Model:	ROI, SMART H.264+/H.265+, flexible coding, applicable to vario	NIC .
		bandwidth and storage environments	ous
		Shutter Speed: 1/2 s to 1/100,000 s	
		Rotation mode/Angle Adjustment: Pan: 0° to 360°, tilt: 0° to 75°, ro	otate: 0° to
		360°	
		➤ Image Enhancement: BLC,HLC,3D DNR	
		Built-in Microphone	
		Abnormality detection: Motion detection, video tampering alarm,	network
		disconnection, IP conflict, illegal access or equivalent	
		> 12V DC/PoE power support	
		IP67 protection or betterShould support Mobile monitoring	
		Should support Mobile monitoring	
2	4MP Outdoor	➤ Image sensor: 1/3-2.4" CMOS	
	Bullet Network	Camera Type: Outdoor	
	Camera	➤ Resolution: 4MP (2560 × 1440) @ 25/30 fps	
	** **	➤ Shutter Time: 1/3 s to 1/100,000 s	
		Day & Night: IR cut filter	
	Brand:	Lens Type: Fixed focal lens: 2.8 and 4 mm optional	
	8	➤ SN Ratio: ≥52 dB	
		Aperture: F1.6 or equivalent	
	Model:	➤ Image Enhancement: BLC,HLC,3D DNR	
		Protection: IP67: IEC 60529-2013 or higher	
		Focal Length: 2.8mm-4mm	
. 1		► Bit Rate Control: CBR, VBR	
		Video Compression: Main stream: H.265+/H.265/H.264+/H.264,	
		Sub-stream: H.265/H.264/MJPEG	
		Power Consumption: 12V DC/PoE Power Supply Operating Temporature: 20 °C to 60 °C (22 °E to 140 °E)	
		Departing Temperature: -30 °C to 60 °C (-22 °F to 140 °F).	1
		Abnormality detection: Motion detection (support alarm triggering specified target types (human and vehicle etc.), video tampering ala conflict	

उं र्वर्थी इ.विकाश भाट स्चना प्रविधि अधिक



3	32 Channel Network	➤ HDD Capacity: up to 10 TB
	Video Recorder	➤ Interfaces: minimum 2 SATA
	D 1	➤ Video output: 1×HDMI, 1×VGA
	Brand:	➤ USB Interfaces: Minimum 2
		Network Interfaces: Minimum 1×RJ-45 port (10/100/1000Mbps)
		➤ Protocols: HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP,
	Model:	DHCP, DNS, IP Filter
		➤ Working Temperature: -10°C to 55°C / Humidity: 10-90% or better
		➤ Incoming Bandwidth: ≥ 160 Mbps
		Decoding Format: H.265/H.265+/H.264/H.264+ or better
		➤ Audio: 1-ch, RCA or BNC
4	10-Port/2 Uplink	➤ Port: 9 10/100M PoE ports, 2 10/100 uplink ports or equivalent
	Switch with 8-Port	➤ Support 802.3af/at standards
	PoE	➤ Transmission range: ≥250 M
		Visualized topology management, Realtime video control and real time
		video alarm push, network health monitor
		➤ Operating Temperature: -10°C to +55°C
5	10 TB HDD	➤ Capacity: 10TB
	Brand:	➤ Speed: ≥ 5,900RPM
	Diana.	➤ Interface Types: SATA
		Cache: 256MB or equivalent
	Model:	
6	Networking Cabinet	> 9U sized rack with default lock system
7	CAT6 Cable	> 305 m (1000 ft)/carton UTP CAT6, Pure Copper power over Ethernet,
		compatible with one cable or equivalent
		High-purity oxygen-free copper conductor or equivalent
		Customized PVC outer sheath; Have certain flame retardant properties or
	2	equivalent
		➤ Meet ANSI/TIA 568.2-D, ISO/IEC11801, reducing damage during the
		project.
	5.0	Should have better electrical properties and transmission performance
8	Delivery,	➤ To Tribhuvan Secondary School, Thakurbaba-1
	Transportation and	Work should be completed within the 7 working days after getting
	Project Completion	purchase/work order.
	Period	
9	Warranty	At least 2 years warranty should be provided with free repairing services
10	Notes	CCTV should be compatible with the existing system
10	110103	
10	110103	If needed one can contact and observe the project location.
10	Trotes	 If needed one can contact and observe the project location. No any extra cost for the project will provided except the mentioned cost in

दुः विकाश भाट इं.विकाश भाट चुचना प्रविधि अधिक रामहरि रिजाल
प्रमासकीय अधिकत



2.Technical Specification of 75 Inches Smart Board (AVR)

Brand	To be specified by the Supplier:		
Model	Model To be specified by the Supplier:		
-	Size	75 Inches	
	Resolution	3840 × 2160 (4K)	
LED Panel	Brightness	At least 350 cd/m ² or higher	
	Response Time	< 8ms	
	Pixel Pitch	0.429(H) mm × 0.429(V) mm	
	Visual angle	178 (H) / 178 (V)	
	Lifespan	At least 40000hrs or higher	
	Refresh rate	60Hz	
	Back Light Type	Direct LED (D-LED) Technology or equivalent	
		LED Interactive Touch Screen	
	Surface Glass	Anti-Glare Glass	
System Drive	 Android system: Minimum Android 9 or higher. At least 8GB memory, 128 GB storage space, using Android OS or equivalent CPU: Quad Core A55 or higher GPU: Built-in GPU Card-G52MP2 or equivalent 		
I/O Port	MINI-AV, PC Audio, VGA, TV-USB 2.0, 2× HDMI, RJ45, USB Port		
Front side	HDMI, USB		
Camera/MIC	Built-in minimum 8MP / Built in microphone		
Front side key	Available		
Bluetooth/WiFi	Inbuilt Bluetooth and WiFi 2.4/5G or better		
USB Support file	Picture: JPEG, BMP, PNG		
format	Video: MPEG1, MPEG2, MPEG4, H264, RM, RMVB, MOV, MJPEG, VC1, DivX, FLV		
	Audio: WMA, MP3, M4A, (AAC)		
Speaker	15 W × 2 or higher Built-in speaker		
Video Features	Split Screen/Multitasking support		

दुं विकाश भाट



OS System	Support Windows 7/ Windows XP/ Windows 2000/ LINUX UNIX/ Windows 8.1 (X86) or		
5	higher version of Windows		
Safety	Necessary arrangement for protecting Interfaces and buttons		
Necessary	Remote controller, Touch Pen, HDMI Cable, Wall mount bracket, hook, user manual and		
Accessories	other necessary items.		
Default System	English		
Language			
Authorization	Must provide authorization letter from manufacturer		
Warranty	At least 3 year or more including parts and services		
Delivery,	To Tribhuvan Secondary School, Thakurbaba-1		
Transportation and	➤ Work should be completed within the 7 working days after getting purchase/work		
Project Completion	order.		

इं.विकाश भाट सूचना प्रविधि अधिकृत प्रमुख प्रशासकीय अधिकृत



3. Technical Specification of 55" Smart LED TV

Parameters		Description	
Brand		To be specified by the supplier: -	
Model		To be specified by the supplier: -	
Screen Size		55 inches	
Resolution		3840×2160 Px or equivalent	
Refresh rate		At least 60Hz	
Storage	RAM	At least 2GB	
Storage	ROM	At least 16GB	
Speaker		At least 10W×2 or higher	
Operating System		Android TV 9 or higher	
Wireless Connectivity		WiFi (2.4GHz/5GHz), Bluetooth 4.2 or higher and should support wireless connections like Miracast	
I/O Ports		3x HDMI (1 contain ARC), 2x USB 2.0, 1x Ethernet (LAN), 1x AV input, 1 x3.5mm headphone jack	
Viewing Angle		170 Degree or more	
Wall Mount		Should be included with the item	
Delivery and Transportation		Throughout Thakurbaba Municipality Area as instructed by Municipal Executive Office Within 15 days of purchase order	
Installation		Free Installation of TV throughout Thakurbaba Municipality Area	
Warranty		At least 2 years	

इं.विकाश भाट



4. Technical Specification of OPS

Parameters	Description
Brand	To be specified by the supplier: -
Model	To be specified by the supplier: -
CPU	At least i5 11 th Generation, 2.4 GHz Processor
RAM	8 GB
Storage	256 GB SSD
Graphics	Intel UHD or Equivalent
Video	Support HDMI 2.0, 4K Video
Others	Antenna: Dual Antenna 802 b/g/n, Wireless Data Transmission
Operating Systems	Pre-installed windows 10 Pro/ Windows 11
Note	OPS Should be compatible with any AVR board and the supplier should connect it with AVR board at free of cost.

उंदे ०४ X. इं.विकाश भाट सचना प्रविधि अधिकृत



5. Technical Specification of A3 Multifunction Duplex Printer

Parameters	Specifications / Descriptions	
Brand	To be specified by the supplier: -	
Model	To be specified by the supplier: -	
Function	Print/Scan/Copy	
Printer Type	Semiconductor Laser / Monochrome Laser Multifunctional	
Duplex Printing	Yes	
Display	≥ 2 Lines	
Memory ≥ 256 MB		
Printing Speed	≥ 20/10 PPM	
Paper Capacity	≥ 400 sheets	
Supported Operating System	Windows Server 2003, Windows Server 2008, Windows Server 2012, Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10 or Higher, Apple Macintosh OS 10.5 or more; Linux OS	
Resolution	≥ 600 × 600 DPI	
Warranty	At least 1-year Warranty	
Note	Supplier has to set-up the printer at the school premises	

ई.विकाश भाट सचना प्रविधि अधिकृत



6. Technical Specification of Speaker:

Parameters	Specifications / Descriptions		
Brand	To be specified by the supplier: -		
Model	To be specified by the supplier: -		
Input Power	≥ 200W RMS		
Configuration	Two Way enabled		
Frequency Response	55-20,000Hz or equivalent		
Low Frequency Speaker	2 × 304.8 mm (12"), Ø 38.1 mm (1.5") Voice Coil or better		
High Frequency Unit	1 × Piezo Horn Tweeter 76.2 mm (3") × 152.4 mm (6") or better		
SPL at (1W/1m)	≥ 100dB		
Max. Rated SPL	≥ 123dB		
Nominal Impedance	$\geq 8\Omega$		
Port	Free Flow Flared or equivalent		
Input Connectors	6.35 mm (1/4") Phone Jack + Terminal Strip or better options enabled		
Note	 Necessary items to connect mixer amplifier to the speaker should provide by the supplier Supplier should provide proper training to operate the Mixture Amplifier and speaker Supplier should provide other necessary items to operate the system 		
Warranty	At least one year warranty		

इं.विकाश भाट सचना प्रविधि अधिक



7. MIXER AMPLIFIERS

Parameters	Specifications / Descriptions			
Brand	To be specified by the supplier: -			
Model	To be specified by the supplier: -			
Power Output	300W + 300W Max., 200W + 200W RMS at 10% THD, 180W + 180W RMS at 5% THD, 165W + 165W RMS at 2% THD or more			
Output Regulation	≥ 2 dB, no load to full load at 1kHz			
Frequency Response	≥ 50-15,000Hz ±3dB			
Tone Controls	Bass: ±10dB at 100Hz, Treble: ±10dB at 10kHz or better			
Signal to Noise Ratio	≥ 60dB			
Input Channels	Mic/Aux: $6 \times$ Mic 0.6 mV/ 4.7 k Ω , $2 \times$ Aux 100 mV/ 470 k Ω , Stereo Music Mode: L/R 200 mV/ 100 k Ω , Line L/R 1 V/ 50 k Ω or more			
Output	Preamp $200 \text{mV}/600\Omega$, Line $1 \text{V}/1 \text{k}\Omega$ or better			
Speaker Output	4Ω , 8Ω , $70V$ & $100V$ for each zone or better			
Digital Player	MP3 Player with USB, SD and MMC Card Reader facility			
Other Features	 Stereo/Mono switch to change ambience of MP3 music player and CD/Stereo music for DJ programs. Separate USB level control should be provided. Built-in MP3 player with remote control and LCD display for USB, SD/MMC card reader. Line Input & Output on each zone for connecting to a Mixer and Booster Amplifier respectively. Preamplifier output for recording. Box Speaker/Driver Unit selector switch for each zone. Bass boost defeated at Driver Unit position for safer operation of driver units. Zone On/Off facility should be provided Resettable circuit breaker for protection against overload and short circuit feature 			
Power Consumption	AC: 700VA DC: 9A or equivalent			
Note	 Necessary items to connect mixer amplifier to the speaker should provide by the supplier Supplier should provide proper training to operate the Mixture Amplifier Supplier should provide other necessary items to operate the system 			
Warranty	At least One year Warranty			

इं.विकाश भाट सूचना प्रविधि अधिकृत

रामहरि रिजाल प्रशासकीय अधिकत



8. Microphones/Mics

Parameters	Specifications / Descriptions		
Brand	To be specified by the supplier: -		
Model	To be specified by the supplier: -		
Wired Microphone	Frequency Response:	≥ 50-15,000Hz	
	Sensitivity:	≥ 2.0mV/Pa- 2.8mV/Pa or better	
	Impedance:	≥ 600Ω	
	Wire/Cord/Cable	≥ 6 meters long	
Wireless Microphone	Frequency Response:	≥ 50-15,000Hz	
	Sensitivity:	≥ 2.0mV/Pa- 2.8mV/Pa or better	
	Impedance:	$\geq 600\Omega$	
	Others	Necessary Connectors/Antenna should be provided	
Note	 Microphones should be compatible with the mamplifier Sound quality must be better 		

इं.विकाश भाट सूचना प्रविधि अधिकृत

रामहीर रिजाल प्रमासकीय अधिकृत